

## 7000CD

## DENTAL LAB STEAM CLEANER

The 7000CD produces up to 65 PSI of steam pressure and reaches temperatures up to 221°F at the tip. It's ideally suited for use in dental labs for cleaning away left over wax, plaster waste and other debris, and for polishing the final product.

Steam deodorizes and sanitizes with heat and moisture and since the only ingredient required for the 7000CD is water, cleaning has never been safer, healthier or more environmentally friendly.

## **SPECIFICATIONS**

| ELECTRICAL           | 120v                               |                          |
|----------------------|------------------------------------|--------------------------|
| WATER CAPACITY       | 2.37 GAL                           | 9L                       |
| OPERATING PRESSURE   | Up to 65 PSI                       | 4.5 BAR                  |
| STEAM TEMPERATURE    | 221°F                              | 105°C                    |
| ELEMENTS             | 2 - 1,200W each (1 spare)          |                          |
| POWER CONSUMPTION    | 10 amps                            |                          |
| TANK CONSTRUCTION    | Stainless steel                    |                          |
| LOW WATER INDICATOR  | Standard                           |                          |
| STEAM CONNECTOR TYPE | Quick-release                      |                          |
| NET WEIGHT           | 31.15 lb                           | 14.12 kg                 |
| SHIPPING WEIGHT      | 34.7 lb                            | 15.7 kg                  |
| PRODUCT DIMENSIONS   | 12.25" x 14.25" x<br>20.5"         | 31 x 36 x 52 cm          |
| SHIPPING DIMENSIONS  | 16" x 14.75" x<br>24.25"           | 40.5 x 37.5 x 61.5<br>cm |
| ELECTRICAL APPROVAL  | cETLus                             |                          |
| WARRANTY             | Limited 1 year, 2 year boiler tank |                          |
|                      |                                    |                          |

## THE POWER OF STEAM



**4 SAFETY SYSTEMS** 



**QUICK RELEASE** 



PRESSURE GAUGE





BLOW DOWN VALVE





THERMOSTAT RESET



4.5 BAR PRESSURE





