

## **SPECIFICATIONS**

ELECTRICAL	120v	
WATER CAPACITY	Unlimited	
BOILER CAPACITY	1.25 GAL	5L
OPERATING PRESSURE	Up to 60 PSI	4 Bar
STEAM TEMPERATURE	221°F	105°C
ELEMENT	2 - 1,200W each (1 spare)	
POWER CONSUMPTION	10 amps	
TANK CONSTRUCTION	Stainless steel	
LOW WATER INDICATOR	Standard	
STEAM CONNECTOR TYPE	Quick-release	
NET WEIGHT	38 lb	17.2 kg
SHIPPING WEIGHT	46 lb	21 kg
PRODUCT DIMENSIONS	11.5" x 11" x 39"	29 x 28 x 99 cm
SHIPPING DIMENSIONS	41.5" x 16" x 18"	105.5 x 40.5 x 45.5 cm
ELECTRICAL APPROVAL	ETL Special Inspection	
WARRANTY	Limited 1 year, 2 year boiler tank	

## 9000CD

## INDUSTRIAL STEAM CLEANER

The 9000CD provides continuous steam for an unlimited amount of time when it's hooked up to a direct water line or with the available 2 gallon water container. There's no more down time waiting for the boiler to re-pressurize. The 9000CD is the perfect choice for environments that require large volumes of uninterrupted steam.

Steam deodorizes and sanitizes with heat and moisture and since the only ingredient required for the 9000CD is water, cleaning has never been safer, healthier or more environmentally friendly.

## THE POWER OF STEAM













BLOW DOWN VALVE









BOILER TANK
2 YEAR WARRANTY

THERMOSTAT RESET

4 BAR PRESSURE

DIRECT WATER FEED





